NECAL CORPORATION

Transfer T	apes
------------	------

Commonly Used Transfer Adhesives

Halistei	Tapes	C	Jillillolliy Oseu	Hallstei	Adilesives		
NECAL	<u>3M</u>	<u>NECAL</u>	<u>3M</u>	<u>Flexcon</u>	<u>MacTac</u>		<u>Ritrama</u>
9170P	467MP	9170P	467MP	201	IF2012		3-1206
9175P	468MP	9175P	468MP	806	IF2015	3-2	055, 3-2074
9175W	6035PL	9501P	9471LE	302	IF1051		3-2042
9501P1/W	7951	9502P	9472LE	807	IF2095		3-2043
9170P1/W	7952MP						
9175P1/W	7955MP						
9170P1/W	7962MP	Stan	dard Sheets Si	ze is 24 in	ches by 36	inches	
9175P1/W	7965MP	Standard F	Roll Sizes are 1	8 inches o	r 24 inches	by 500	feet.
9501P1/W	8132LE						
9502P1/W	8153LE	Mast	er Rolls Width	s are 48 ir	nches to 54	inches	
9072P	9442	Cut rolls to (Customer Spec	ifications	: 10 inches	to 55.5	inches
9074P	9445		Standard Core	Diameter	: 3 & 6 inch	es	
9502P	9453LE						
9072P	9460PC		NECAL	CORPORA	ATION		
9074P	9469PC			uth Water			
9501P	9471			ta, WI 546			
9501P	9471LE		•	•			
9501P	9471PC			8.269.300			
9502P	9472		www	w.necal.co	om		
9502P	9472LE						
9072P	9482PC						
9074P	9485PC						
9170P	9502	R	oHS, REACH, D	ecaBDE, I	Proposition	65	
9175P	9505		And Conflict	Mineral C	Compliance		
9170P1/W	9552		PS ⁻	TC & ASTI	VI		
9175P1/W	9555		ISO	9001:201	L 5		
9502W	9653LE		Fit-fo	r-Use Tes	ting		
9170W	9667MP						
9175W	9668MP						
9501W	9671						
9501W	9671LE						
9502W	9672	Require	a unique solut	tion to a p	erplexing o	halleng	ge?
9502W	9672LE	NECAL can coat	t & convert adl	hesive pro	ducts mee	ting yo	ur specific
9170W	9772WL		reg	uirement	S.		-
9175W	9774WL	041 1	•	-			
9175W		Stick	c va/it		10		
	9774WL	Otior	/ AAIC	11 /	10		

JAN2023 **NECAL CORPORATION**

NECAL CORPORATION

Double – Side Coated Transfer Foams

<u>Product</u>				
<u>Name</u>	<u>Description</u>	Foam Type	<u>Color</u>	Thickness/Mils
8195	General Purpose-Open Cell	Polyurethane	Gray	35
8199 Series	High Temperature-Closed Cell	Polyurethane	Black	15,30,45,60,90,110,125,180
8292	Low Surface Adhesive -Closed Cell	Polyolefin Blend	Black	35
8495	High Temperature-Open Cell	Polyurethane	Black	35
8799	Low Surface Adhesive -Closed Cell	Polyurethane	Black	15,30,45,60,90,110,125,180

Supported Adhesives with a Scrim (carrier)

Product Name	MILS	<u>Carrier</u>	MILS	Adhesive Type
8608	3.5	1.5 Mil Non-Woven	3.0	LSE
9512	1.75	.00048 Mil Polyester	1.75	LSE
9513	2.0	.00048 Mil Polyester	2.0	LSE
9515	2.5	1 Mil Polyester	2.0	LSE
9516	3.5	.00048 Mil Polyester	2.25	LSE
9517	4	1 Mil Polyester	2.0	LSE

Unique Thermoplastic

Product Name 5130 Designed to be resistant to blocking, so it needs no release liner. NECAL 5130 has the unique capability of bonding to a wide variety of substrates, including glass, wood, aluminum, steel, brass, various cloths and leathers, and most plastics (ABS, styrene, nylon, polyethylene, and polypropylene). In addition, NECAL 5130 has excellent resistance to water, oil, gas, and most detergents and has excellent low-temperature properties.

Mission

We provide innovative coating solutions and services by empowering people to passionately collaborate through relationships as permanent as our adhesives!

NECAL produces and sells quality adhesive products with our suppliers and employees. We are committed to working and learning as a team, continually improving our business processes, and providing customer service excellence. By doing so, we aim to grow our presence in the marketplace and preserve a legacy for future generations.

Stick with Us



NECAL CORPORATION JAN2023